

The SILI CWF pulverizing pump is a kind of open impeller centrifugal pump, is used for pulverizing and transferring the soft sludge and sewage in the sanitary or sewage treatment device water under 80 C degree. The max diameter of solid particle after pulverizing is with 5mm.

There are cutting blades at the edges of the impeller and the suction port of the pump.

Double face special mechanical seal is used on sides the pump shaft.

Easily opening the suction port, to remove the sludge inside the pump casing.

Motor is in Y-H marine industry type.



Model	Capacity (m3/h)	Head (m)	Power (kw)	Inlet flange (DN,mm)	Outlet flange (DN,mm)	Size(L*W*H) (mm)	Weight (kw)
0.5CWF-8	5	8	0.75	50	32	350*200*200	25
0.5CWF-10	5	10	1.1	50	32	350*200*200	26
0.5CWF-15	5	15	1.1	50	32	350*200*200	30
0.5CWF-20	5	20	1.5	50	32	350*200*200	30
0.5CWF-25	5	25	2.2	50	32	350*200*200	30
0.5CWF-30	5	30	3.0	50	32	350*200*200	35
1CWF-11	10	11	1.5	65	32	400*250*220	35
1CWF-20	10	20	3.0	65	50	400*250*220	45
1CWF-25	10	25	4.0	65	50	400*250*220	55
1CWF-30	10	30	5.5	65	50	400*250*220	55
1.5CWF-20	15	20	3.0	65	50	420*250*220	45
1.5CWF-25	20	25	4.0	65	50	420*250*220	55
2CWF-11	20	11	2.2	65	40	420*250*220	45
2CWF-20	20	20	4.0	65	40	420*250*220	65
2CWF-30	20	30	7.5	65	50	420*250*220	75
3CWF-10	30	10	4.0	65	50	500*280*250	75

**SILI PUMP,**  
**Your reliable one-stop supplier of marine pumps.**

Shanghai SILI PUMP Industry Co., Ltd.

Add: No.128 Jinyuan Road, 201518, Shanghai, China (Jinyuan Industry Area)

Tel: 0086-21-39109967, fax: 0086-21-39109967

Web: [www.silipump.com](http://www.silipump.com) e-mail: [sales@silipump.com](mailto:sales@silipump.com)